



EASY REPLACEMENT
 No Tools Means No Tools!



RE

RE RED SERIES FILTERS

Red series filters are high flow rate pleated filtration solutions with extended life and use, with filtration levels of 1 absolute, 5, 20, 50, and 150 microns, along with an activated carbon (PAC) solution. The filters are designed with a large filtration layer that extends filtration level contamination and service life while achieving high flow rates up to 150 GPM (568 LPM) and low pressure drop.

The filters will outperform competitive filtration solutions in all turbidity applications, including silt, rust, and other particle filtration. The red series also provides lower shear water velocity as the raw water passes through the filter, allowing for more contact time and interaction with the extensive surface area of the filters. This results in higher water quality and longer life of the filtration system.

A direct replacement for expensive stainless steel housings, red series filters have significant surface area, low pressure drop, and high flow rate capabilities. The filters are ideal as polishing or pre-filters in applications requiring fine filtration and high capacity. Cleanable from 5 microns and up and utilizing 100% cellulose free media, these are the commercial filtration solutions of the future!

Each filter comes with a unique handle designed top cap for lightweight and easy removal, a bag for proper disposal, and a double O-ring connection. All components and materials are manufactured from NSF 61 and FDA Certified materials.

Red series filters are available in the following configurations:

- CT-COMM1A:** 1 micron absolute pleated PP
- CT-COMM05:** 5 micron PP pleated
- CT-COMM20:** 20 micron PP pleated
- CT-COMM50:** 50 micron PP pleated
- CT-COMM150:** 150 micron PP pleated
- CT-COMM-CARB:** Pleated activated carbon

FEATURES

- Durable and chemical resistant polypropylene filter and cap construction
- Double EPDM O-ring seals
- Filter belly bands
- Unique filter handle design

BENEFITS


Extended service life, contaminant removal, and dirt holding capacity	Insures no bypass of contaminants and high chemical compatibility
Low pressure drop = high flow	Bacteria and chemical resistant
Ease of filter removal from housing	Prevent collapsing of filters under high flow or contaminant load applications

APPLICATIONS

- Ideal for residential, food service, rental fleets, commercial and industrial applications
- Make-up water, RO pre-filtration, cooling towers, chill water loops, metal finishing
- Process water (turbidity, particulate, colloidal suspensions)
- Community water, livestock and poultry water systems
- Replacement of bag filters with more surface area and capacity
- Other water-based fluid solutions

FILTER PERFORMANCE

Low Pressure Drop ONE™ filters are designed to minimize pressure drop by using 2" pipe fittings and large diameter center tubes (see chart for pressure drop data using pleated cartridges).



EASY REPLACEMENTS NO TOOLS REQUIRED

1. PRESS THE RED PRESSURE RELIEF VALVE TO UNSEAT THE RING



2. REMOVE SNAP RING



3. LIFT TOP CAP



BETTER FILTRATION THERE'S NO COMPETITION

Activated carbon (PAC) filter: Service flow rates up to 15 GPM (57 LPM) with a removal capacity up to 150,000 gallons and a 90% chlorine reduction—improving taste, odor, sediment, and chlorine

Maximum pressure differential: 40 psi

Maximum flow rate of 1 micron absolute: 50 GPM (190 LPM)

Maximum flow rate of all other configurations: 150 GPM (568 LPM)

AVAILABLE OPTIONS AND CONFIGURATIONS



ITEM #: CT-1/4NPTLID

Top cap option with pressure release valve and removal handles



ITEM #: CT-4.5LID

4.5" threaded top/bottom commercial cap with threaded connection



ITEM #: CT-RETAININGRING

Snap ring with I.D. tag connection



ITEM #: CT-4.5DRAIN
CT-4.5ADAPTER

4.5" bottom drain plumbing for commercial filters